



55" Dual DTEN D7

SPECIFICATIONS

All-in-One Video
Conferencing Solution for
Unparalleled Collaborations



reddot award 2019
best of the best

*D7 in this image is not in 1:1 ratio



| | | | |
|---------------|---|-------------------------------------|--|
| PRODUCT | D7 55" Dual | INPUTS AND OUTPUTS | HDMI Out x 1 USB 3.0 x 1 3.5-mm Audio Jack x 1 Microphone x 1 Ethernet LAN (RJ45) x 1 |
| SOFTWARE | DTEN D7 OS, provisioned by D7 OS | POWER | Auto-Sensing Power Supply 100 to 240 VAC, 50 to 60 Hz |
| ALL-IN-ONE D7 | LED 55" Multi-Touch Display x 2 4K Camera 16-Microphone Array Integrated Speakers | VESA | 400 x 300 mm |
| DISPLAY | LED 55" x 2, 4K, 16:9 Capacitive Touch Screen | PRODUCT DIMENSIONS (Each Unit) | 49 x 30.5 x 2.13 in (124.49 x 77.38 x 5.42 cm) |
| CAMERA SYSTEM | Fixed Lens, Infinite Focus F-value: 2.8 4K Diagonal Field of View (FOV): 86 Degrees Unit Mounted Tilt: 15 Degrees | PRODUCT WEIGHT (Each Unit) | 50.7 lb (23 kg) |
| AUDIO SYSTEM | 16 Elements Microphone Array Integrated 2-Channel Stereo Speakers High Quality 20-kHz Audio Zoom Rooms Acoustic Echo Cancellation Automatic Gain Control (AGC) Automatic Noise Reduction | PACKAGE DIMENSIONS (Single Package) | 56 x 36 x 8.5 in (142 x 92 x 21.5 cm) |
| NETWORK | Ethernet (RJ-45) 100/1000 Mbps Wi-Fi 802.11a/b/g/n, 802.11ac (2.4 and 5 GHz) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP/HTTPS Proxy Support | PACKAGE WEIGHT (Single Package) | 77 lb (35 kg) |
| | | OPERATING TEMPERATURE AND HUMIDITY | Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH |
| | | LANGUAGE SUPPORT | English * Additional languages to be supported in future software release |
| | | SYSTEM REQUIREMENT | Zoom Rooms License |
| | | APPROVALS AND COMPLIANCE | FCC, CE, CCC, ROHS, ACMA, CB PSE, TELEC, BIS |

*Specifications are subject to change without prior notice.

Zoom Rooms Simplified • Affordable



UK.GORILLACLOUDSERVICES.COM | INFO@GORILLACLOUDSERVICES.COM