



# 75" DTEN D7

## SPECIFICATIONS



reddot award 2019  
best of the best

\*D7 in this image is not in 1:1 ratio

All-in-One Video  
Conferencing Solution for  
Unparalleled Collaborations



PRODUCT	D7 75"
SOFTWARE	DTEN D7 OS, provisioned by D7 OS
ALL-IN-ONE D7	LED 75" Multi-Touch Display Flexible Top/ Bottom 4K Camera Placement 16-Microphone Array Integrated Speakers
DISPLAY	LED 75" , 4K , 16:9 Capacitive Touch Screen
CAMERA SYSTEM	Fixed Lens, Infinite Focus F-value: 2.8 4K Diagonal Field of View (FOV): 86-Degrees, Adjustable to 120-Degrees Unit Mounted Tilt: 15 Degrees
AUDIO SYSTEM	16 Elements Microphone Array Integrated 2-Channel Stereo Speakers High Quality 20-kHz Audio Zoom Rooms Acoustic Echo Cancellation Automatic Gain Control (AGC) Automatic Noise Reduction
NETWORK	Ethernet (RJ-45) 100/1000 Mbps Wi-Fi 802.11a/b/g/n, 802.11ac (2.4 and 5 GHz) IPv4 Dynamic Host Configuration Protocol (DHCP)/ Static HTTP Proxy Support

INPUTS AND OUTPUTS	HDMI Out x 1 HDMI In x 1 USB 3.0 x 1 3.5-mm Audio Jack x 1 Microphone x 1 Ethernet LAN (RJ45) x 1
POWER	Auto-Sensing Power Supply 100 to 240 VAC, 50 to 60 Hz
VESA	400 x 800 mm
PRODUCT DIMENSIONS	66.1 x 37.9 x 2.19 in (167.87 x 96.29 x 5.54 cm)
PRODUCT WEIGHT	83.6 lb (38 kg)
PACKAGE DIMENSIONS	73.4 x 44.7 x 7.7 in (186.5 x 113.5 x 19.5 cm)
PACKAGE WEIGHT	94.6 lb (43 kg)
OPERATING TEMPERATURE AND HUMIDITY	Operating Temperature 0°C to 40°C Storage Temperature -10°C to 60°C Operating Humidity 20% to 80% RH Storage Humidity 10% to 60% RH
LANGUAGE SUPPORT	English * Additional languages to be supported in future software release
SYSTEM REQUIREMENT	Zoom Rooms License
APPROVALS AND COMPLIANCE	FCC, CE, CCC, ROHS, ACMA

\*Specifications are subject to change without prior notice.

## Zoom Rooms Simplified • Affordable



UK.GORILLACLOUDSERVICES.COM | INFO@GORILLACLOUDSERVICES.COM